

Tendon force vs. frame response

Test Problem

Name:	Tendon force vs. frame response
Description:	Tendon application is validated by comparing tendon forces to those in an equivalent frame system.
Program:	SAP2000
Version:	12.0.2
Model ID:	na

On this page:

- [Overview](#)
- [Model screenshots](#)
- [See Also](#)
- [Attachments](#)

Overview

The model attached contains four separate structures, shown below in Figures 1 and 2, and listed as follows:

- Two-span bridge created using the [bridge modeler](#)
- Two-span bridge created manually
- One-span bridge created using the bridge modeler
- One-span bridge created manually

All four structures have the following properties:

- Each span length is 10m.
- Concrete deck sections are 0.5m deep and 3m wide.
- Simply-supported conditions are at each abutment and [bent](#).
- A straight [tendon](#), 25mm in diameter, runs along each length. Tendons are prestressed to 10kN (without losses) and located 0.05m from the bottom of each section.

The purpose of this model is to:

- Determine and review internal forces resulting from prestressing.
- Verify the prestressing forces used for flexural design check.
- Compare [frame-element](#) forces to the prestressing forces, found through the Display > Show Bridge Forces/Stresses menu.
- Define a section cut through the frame and tendon, review forces, and compare with frame and tendon response at section cut locations.

Model screenshots

Flexural response is depicted in Figures 1 and 2:




Figure 1 - Moment diagram, two-span bridge with tendon

- [SAP2000 V12.0.2 model](#) (zipped .SDB file)